



AIMING ADJUSTMENT FOR LANTERN MOUNTING STRAPS

- THE TOP LOCK WASHER CAN BE ROTATED IN STEPS OF 28° (DIMPLE TO DIMPLE).
- THIS ANGLE CAN BE HALVED TO 14° BY ROTATING EITHER LOCKWASHER 180°.
- THE NORMAL MANUFACTURING CLEARANCES WILL PROVIDE AN ADJUSTMENT OF 5° EITHER WAY BEFORE THE NUTS ARE TIGHTENED.

A	ORIGINAL ISSUE	April '09	IC 12/10	PC 01/11
ISSUE	AMENDMENT	DRAWN DATE	CHK'D DATE	APPR'D DATE

DESIGN AUTHORISED FOR ISSUE			
P. COTTON SIGNATURE ON ORIGINAL			
MANAGER CITY ASSETS - R.P.E.Q: <u>2546</u>			
DESIGN APPROVED			
I. CONDRIK SIGNATURE ON ORIGINAL DATED 12/10			
PRINCIPAL ENGINEER ROAD NETWORK INFRASTRUCTURE - R.P.E.Q: <u>8591</u>			
DESIGN	Brisbane Infrastructure	DATE	April '09
DRAWN	Brisbane Infrastructure	DATE	April '09
CHECKED	I. Condric	DATE	Dec '10
DRAWING FILENAME	UMS 600_046		
ASSOCIATED PLANS			



BRISBANE CITY COUNCIL STANDARD DRAWING

**ASSEMBLY DETAIL
OF LOCK WASHERS**

SCALE		NOT TO SCALE	
DWG No.		UMS 600/046	
ORIGINAL SIZE	A3	REVISION	A