



COLOURED AGGREGATE SPRAY SEAL PATH – SECTION

LANDSCAPE AS SPECIFIED.
 100x100mm CONCEALED CONCRETE EDGE IF SPECIFIED.
 COLOURED AGGREGATE SPRAY SEAL – REFER TO UMS 711 FOR LIST OF APPROVED SUPPLIERS. INSTALL TO MANUFACTURERS SPECIFICATIONS.
 150mm SUBBASE COURSE CBR 45 COMPACTED TO 95% MOD. M.D.D. ENSURE SUBBASE EXTENDS 100mm MIN. BEYOND CONCRETE EDGE.
 COMPACTED SUB-GRADE TO 100% STANDARD M.D.D. ENSURE COMPACTED SUB-GRADE EXTENDS 100mm MIN. BEYOND CONCRETE EDGE.

GENERAL NOTES

ENSURE MOWN HEIGHT OF GRASS (TURF) AREA FINISHES FLUSH WITH PATH EDGE.
 ENSURE GARDEN AREAS (MULCH) FINISH 25mm BELOW ADJACENT F.S.L.'s OF PAVEMENT AREAS.
 ALL PATHS TO HAVE 1:50 MINIMUM CROSSFALL.
 ENSURE PARK ELEMENTS ARE LOCATED IN ACCORDANCE WITH DETAILED LANDSCAPE PLAN, AND SUBDIVISION AND DEVELOPMENT GUIDELINES.
 ENSURE PATHS ARE CLEANED OF CONCRETE SLURRY OR SPRAY WHEN INSTALLED TO PREVENT STAINING OR DAMAGE TO APPLIED FINISHES.
 ALL CONCRETE TO BE MINIMUM GRADE N25.
 FOR SLIP RESISTANCE REQUIREMENTS, REFER "REFERENCE SPECIFICATIONS FOR CIVIL ENGINEERING WORK" – S150 ROADWORKS.
 PATHWAYS & PAVEMENTS TO COMPLY WITH AUSTRALIAN STANDARDS AND COUNCIL REQUIREMENTS FOR ACCESS & MOBILITY (AS 1428-2003).
 DIMENSIONS IN MILLIMETRES. (U.N.O).

ISSUE	AMENDMENT	DRAWN DATE	CHK'D DATE	APPR'D DATE
A	ORIGINAL ISSUE	Dec '03	Jul '14	PC 19/04

DESIGN AUTHORIZED FOR ISSUE PAUL COTTON SIGNATURE ON ORIGINAL DATED 12/19/14 MANAGER INFRASTRUCTURE MANAGEMENT R.B.E.O. 2516 DESIGN APPROVED LAREN TEMPLEMAN SIGNATURE ON ORIGINAL DATED 31/08/14 PRINCIPAL PROGRAM OFFICER PARKS		DESIGN DRAWN CHECKED DRAWING FLENAME ASSOCIATED PLANS	CITY DESIGN - L.A. CITY DESIGN - L.A. UMS 746.dwg UMS 746.dwg	DATE DATE DATE	Dec '03 Dec '03 Jun '04
---	--	---	--	----------------------	-------------------------------



BRISBANE CITY COUNCIL - URBAN MANAGEMENT DIVISION

PATH – COLOURED AGGREGATE SPRAY SEAL

SCALE: 1:10
 TITLE: UMS 746
 ORIGINAL SIZE: A3
 REVISION: A